IDWEST Monitoring and Remediation Adapters

dicken ™ PITLESS ADAPTERS

Features: • Brass insert is electroless nickel plated to resist harsh environment and contamination

- Ideal for use in remediation wells
- Precision machined all red brass castings with viton o'rings
- Wrench grip on ell speeds installation
- Large inner and outer gasket to seal out surface water contamination
- Built-in lowering eyelet for easier installation
- Pressure Tested to 150 PSI

Part Number	Model	Discharge Pipe(In.)	Supply Pipe(In.)	Casing Size(In.)	Hole Size(In.)	Shipping Wt. (Lbs-Oz)	Working Load(Lbs.)
952111	LD-S-10-N	1	1	5 to 12	1 3/4	48	2000
952113	LD-S-12-N	1 1/4	1 1/4	5 to 12	2 1/4	58	2000
952021	S-20-N	2	2	5 5/8 to 12	3 1/8	144	5000

* Note all stainless steel adapters available for leachate applications

MAASS™ MODEL JN SERIES OF PITLESS ADAPTERS AND UNITS

- Features:
 Ideal for remediation wells
 - Water contacts only 304 stainless steel nipple and electroless nickel plated brass insert
 - Tapered 8 degree slip fitting for easy installation and removal of electroless nickel plated brass insert
 - No obstruction left in well when insert is pulled
 - Viton O-rings standard
 - 304 stainless steel guide pins standard

MAASS™ MODEL JN WELD-ON PITLESS ADAPTERS

Features:
 Permanently installed by welding for increased strength and durability

Part Number	Model	Discharge Pipe	Drop Pipe	I.D. Casing Size	Weight (Lbs.)
928101	4 J 1 N	1	1	45	6
928121	6 J 1 N	1	1	678+	6
928106	4 J 1 1/4 N	1 1/4	1 1/4	45	7
928126	6 J 1 1/4 N	1 1/4	1 1/4	678+	7
928136	6 J 2 N	2	2	678+	12
928146	8 J 3 N	3	3	81012+	32





MAASS[™] MODEL JCN CLAMP-ON PITLESS ADAPTERS Features: ◆ Ideal for use on either plastic or steel well casing

- ◆ 304 stainless steel clamps and nuts
- Electroless nickel plated brass insert and Viton o'rings standard

		•			•
Part Number	Model	Discharge Pipe	Drop Pipe	O.D. Casing Size	Standard Clamp-On Weight
928302	4JC1 N	1	1	4 1/2	11.0
928307	50DJC1 N	1	1	5	11.0
928312	5JC1 N	1	1	5 9/16	11.0
928322	6JC1 N	1	1	6 5/8	11.75

©2011, MAASS Midwest Manufacturing, Inc.



IDWEST MANUFACTURERS OF QUALITY WATER WELL ACCESSORIES

U.S. & CANADA 1-800-323-6259 • FAX 1-847-669-3230 www.maassmidwest.com P. O. Box 547, 11283 Dundee Road, Huntley, IL 60142-0547 • (800) 323-6259 • IL AREA (847) 669-5135





MIDWEST-DICKEN™ WELD PROCESS MONITOR WELL POINTS

Features:
 Ideal for use in remediation wells

DWEST

- Points will not easily collapse while being driven
- Rugged design with octagonal electroless nickel plated head to prohibit turning in tough driving
- Easily extended in the field by removing head and coupling together with second well point for added capacity
- Stainless steel mig weld top and bottom to prohibit jacket shift or peeling
- 3/16" diameter spotweld on 1" centers to prevent seam opening
- Stainless steel jacketed 1/8" staggered perforations for maximum open area
- Available in 60-80-100 mesh stainless steel gauze for long life screening
- Point may be driven or used with hollow stem flight auger

Part Number	Model Number	Gauze	Pipe Size	Pipe Lg. x Jacket	Weight (Lbs.)
918000	SS90M	60	1 1/4	24 x 18	6
918005	SS90M	80	1 1/14	24 x 18	6
918010	SS94M	60	1 1/4	30 x 24	7
918015	SS94M	80	1 1/4	30 x 24	7
918020	SS98M	60	1 1/4	36 x 30	8
918025	SS98M	80	1 1/4	36 x 30	8
918030	SS100M	60	1 1/4	42 x 36	10
918035	SS100M	80	1 1/4	42 x 36	10
918040	SS102M	60	1 1/4	48 x 42	11
918045	SS102M	80	1 1/4	48 x 42	11
918050	SS110M	60	1 1/4	60 x 54	13
918055	SS110M	80	1 1/4	60 x 54	13
918060	SS164M	60	2	30 x 24	12
918065	SS164M	80	2	30 x 24	12
918070	SS168M	60	2	36 x 30	14
918075	SS168M	80	2	36 x 30	14
918080	SS172M	60	2	48 x 42	18
918085	SS172M	80	2	48 x 42	18
918090	SS176M	60	2	60 x 54	22
918095	SS176M	80	2	60 x 54	22

NOTE: 1 1/4" WELL POINT HAS 2" O.D. 2" WELL POINT HAS 3" O.D.



DRIVE COUPLINGS — ELECTROLESS NICKEL PLATED

Part	Pipe	App. Weight	Quantity
Number	Size	(Lbs.)	per Box
941590	1 1/4	1.0	25
941592	2	1.5	15

DRIVE CAPS — BLACK MALLEABLE

Part Number	Pipe Size (Inches)	App. Weight (Lbs.)	Quantity per Box
930562	1 1/4	1.5	25
930568	2	3.25	10

©2011, MAASS Midwest Manufacturing, Inc.







IDWEST MANUFACTURERS OF QUALITY WATER WELL ACCESSORIES

U.S. & CANADA 1-800-323-6259 • FAX 1-847-669-3230 www.maassmidwest.com P. O. Box 547, 11283 Dundee Road, Huntley, IL 60142-0547 • (800) 323-6259 • IL AREA (847) 669-5135



MAASS

IDWEST Monitoring and Remediation Accessories

MAASS[™] LOCKING WELL CAP

Features:

- Moderate cost with corrosion resistant cast aluminum
- Suitable for use on monitoring wells
- Protection against vandalism
- Easy to install. Drill one hole for bolt to hold cap in place.
 Bolt cap down. Lock padlock through locking tab on cap

Part	Model	O.D. Casing	
Number	Number	Size	Description
952770	4LCS	4 1/2	Submersible
952772	5LCS	5 9/16	Submersible
952774	6LCS	6 5/8	Submersible
952776	8LCS	8 3/4	Submersible
952769	LJ2	PADLOCK FOR CA	PS - ALL KEYED ALIKE

STAINLESS STEEL MALE ADAPTERS

Part Number	Trade Number	Pipe Size (Inches)	App. Weight per 100 Lbs.
406520	MASS-2	1/2	15
406523	MASS-3	3/4	22
406526	MASS-4	1	35
406529	MASS-5	1 1/4	52
406532	MASS-8	2	92

COUPLINGS 304 STAINLESS STEEL SCHEDULE 40

Part Number	Pipe Size (Inches)	App. Weight per 100 Lbs.	Quantity per Box
941594	1	.75	25
941595	1 1/4	1	25
941597	2	1.5	15

©2012, MAASS Midwest Manufacturing, Inc.

DWEST MANUFACTURERS OF QUALITY WATER WELL ACCESSORIES

U.S. & CANADA 1-800-323-6259 • FAX 1-847-669-3230 www.maassmidwest.com P. O. Box 547, 11283 Dundee Road, Huntley, IL 60142-0547 • (800) 323-6259 • IL AREA (847) 669-5135



MADE in the US





MEMBER:

CAPM

MAASS - BASKI MODEL MB PITLESS UNIT HEAVY DUTY MODEL

- EXCELLENT FOR LARGE REMEDIATION APPLICATIONS
- ALL WET PARTS 304 STAINLESS STEEL

Typical Submersible Pitless Unit


The Model MB[™] Pitless Unit is designed for the driller, pump contractor and owner by incorporating new concepts for quick delivery, installation ease and convenience in setting and pulling pumps.

(Vertical Turbine and Booster Pump Station Units are available.) Water tight, heavy duty steel cap Stainless steel screened well vent Neoprene cap gasket Locking bolts available to secure steel cap, and prevent well tampering Rounded corner helps prevent scraping wires Electrical junction box is out of the way and protects wire during pump work Upper casing barrel, supplied by factory or by installer Two large size access holes our centering blocks help for wire, airline, chlorination. prevent "O ring" damage controls, etc. Heavy wall housing Stainless steel rings insure a positive long life seal for "O rings" Weld-on discharge; flanged, threaded, and slip on ends are available Stainless steel spool has large water passages and is of heavy duty construction Weld-on connection to well casing; threaded and compression fittings are available. **QUALITY DESIGN FEATURES** Patented For 8, 10, 12, 14, 16, 18, 20, 22, 24 inch and larger wells.

2" through 12" discharge.

©2011, MAASS Midwest Manufacturing, Inc.

MEMBER



U.S. & CANADA 1-800-323-6259 • FAX 1-847-669-3230 www.maassmidwest.com

P. O. Box 547, 11283 Dundee Road, Huntley, IL 60142-0547 • (800) 323-6259 • IL AREA (847) 669-5135