

YARD HYDRANTS

Features:

- Provides running water all year for farms, homes and industry despite freezing temperatures. 3/4" inlet on brass valve.
- Standard 3/4" brass hose thread adapter on the outlet, and can be removed to connect 1/2" pipe.
- All hydrants are 27" from ground to outlet above the bury depth, using 1" I.D. galvanized steel pipe.
- Hydrant is designed with shut-off valve below frost line. Will not freeze as pipe drains through a bleeder. Brass nozzle is threaded for standard 3/4" garden hose coupling. 7/16" valve rod operates valve below frost line, allowing water to flow even in sub-zero weather. If water leaks at packing nut when hydrant is in operation, tighten nut or replace packing if necessary.



Part Number	Model Number	1" I.D. Pipe Size and Bury Length	Weight Each (Lbs.)	List Price Each
935401	5401	1 ft.	13 - 1/3	See separate price list
935402	5402	2 ft.	15 - 1/2	
935403	5403	3 ft.	17 - 1/2	
935404	5404	4 ft.	19 - 1/2	
935405	5405	5 ft.	21 - 1/2	
935406	5406	6 ft.	23 - 1/2	
935407	5407	7 ft.	25 - 1/2	
935408	5408	8 ft.	27 - 1/2	

HYDRANT REPAIR PARTS

Part Number	Model Number	Description	List Price Each
932901	G-1	Head Casting	See separate price list
932903	G-6	Brass Hose Thread Adapter	
932910	G-10	Lever Casting	
932918	G-15	Lever Bolt	
932920	G-20	Draw Straps	
932921	G-25	Pivot Connector & Nuts	
932927	G-30	Packing Nut	
932930	G-35	Valve Stem Packing	
932940	G-40	Valve Body	
932941	G-45	Operating Rod (SS)	
932942	G-50	Brass Reducer	
	G-55	Operating Stem (7/16" Galv. Rod)	
	G-60	1" Galvanized Pipe	
932945	G-65	Brass Plunger Bushing	
932946	G-70	Brass Plunger Body	
932947	G-75	Brass Plunger Bolt	
932950	G-80	Brass Threaded Washer	
932985	G-85	Rubber Seat Washer (Std. Bibb)	
932986	G-90	Stainless Steel Plunger Spring	
932987	G-100	Retainer Screw for Rubber	
932905	G-105	Cup Leathers	
932988	G-110	Brass Washers for Plunger	
932915	G-115	Plunger Assembly	
932989	G-120	Head Assembly	

G-115 consists of Parts No. G-65, G-70, G-75, G-80, G-85, G-90, G-100, G-105 and G-110.