

MAASS™ PITLESS ADAPTERS



MAASS MODEL J SERIES OF PITLESS ADAPTER AND UNITS ALL FEATURE:

- Water contacts only 304 stainless steel and brass, eliminates rust, corrosion, and electrolysis in the adapter
- Durable cast steel housing
- Tapered 8° slip fitting for easy installation and removal of brass insert
- No obstruction left in well casing when brass insert is pulled
- Designed for shallow or deep settings and high working pressures
- Water System Council - PAS-97 (04) listed

MAASS MODEL J WELD-ON PITLESS ADAPTER Patented

- Features:
- Permanently installed by welding for increased strength and durability
 - J Series of adapters and units available with stainless steel, nickel-bronze inserts, stainless steel housings, and viton or teflon O-rings
 - Only two one inch outlet size Model J Pitless needed to fit all well casing sizes



Part Number	Model	Discharge Pipe	Drop Pipe	I.D. Casing Size	Weight (Lbs)	Working Load(lbs)	List Price Ea.
928100	4 J 1	1	1	4-5	6.0	4000	See separate price list
928105	4 J 1 1/4	1 1/4	1 1/4	4-5	7.0	5000	
928110	4 J 1 1/2	1 1/2	1 1/2	4-5	8.5	5000	
928115	5 J 2	2	2	5	12.0	6000	
928120	6 J 1	1	1	6-7-8+	6.0	4000	
928125	6 J 1 1/4	1 1/4	1 1/4	6-7-8+	7.0	5000	
928130	6 J 1 1/2	1 1/2	1 1/2	6-7-8+	8.5	5000	
928135	6 J 2	2	2	6-7-8+	12.0	6000	
928140	6 J 2 1/2	2 1/2	2 1/2	6-7-8+	18.0	8000	
928145	8 J 3	3	3	8-10-12+	32.0	10000	
928150	10 J 4	4	4	10-12-14+	50.0	15000	

MAASS MODEL JJ WELD-ON PITLESS ADAPTER

FOR SUCTION PUMPS Patented

- Features:
- Lateral (2") can be pressurized to meet state codes
 - Wisconsin and Michigan State approved



Part Number	Model	Discharge Pipe	Drop Pipe	I.D. Casing Size	Weight (Lbs)	Working Load(lbs)	List Price Ea.
928200	4 JJ 1	1	2	4-5	13.0	4000	See separate price list
928205	6 JJ 1	1	2	6-7-8	13.0	4000	
928210	4 JJ 1 1/4	1 1/4	2	4-5	14.0	5000	
928215	6 JJ 1 1/4	1 1/4	2	6-7-8	14.0	5000	

MAASS MODEL JC CLAMP-ON PITLESS ADAPTER Patented

- Features:
- 304 stainless steel clamps and nuts
 - Cast steel lips support adapter housing on wall of well casing; no lock needed
 - Ideal for use on either plastic or steel well casing
 - Buna N rubber gasket seals cast steel housing against O.D. of well casing at point of attachment
 - Model JC available with stainless steel inserts and viton or teflon O-rings



Part Number	Model	Discharge Pipe	Drop Pipe	O.D. Casing Size	Weight	Working Load(lbs)	List Price Ea.
928300	4JC1	1	1	4 1/2	11.0	4000	See separate price list
928305	50DJC1	1	1	5	11.0	4000	
928310	5JC1	1	1	5 9/16	11.0	4000	
928315	60DJC1	1	1	6	11.75	4000	
928320	6JC1	1	1	6 5/8	11.75	4000	
928325	7JC1	1	1	7	12.0	4000	
928330	4JC1 1/4	1 1/4	1 1/4	4 1/2	11.75	4000	
928335	50DJC1 1/4	1 1/4	1 1/4	5	11.2	4000	
928340	5JC1 1/4	1 1/4	1 1/4	5 9/16	11.2	4000	
928345	60DJC1 1/4	1 1/4	1 1/4	6	12.75	4000	
928350	6JC1 1/4	1 1/4	1 1/4	6 5/8	12.75	4000	
928355	7JC1 1/4	1 1/4	1 1/4	7	13.0	4000	

● NOTE: May be installed with 4 1/2" hand grinder and cutting wheel or cutting torch

MAASS PITLESS ADAPTERS